



PB VW III LED DISPLAY

Model	VW III 2,5	VW III 4	VW III 4X
Pixel Pitch (mm)	2,5	4	4
Brightness	1200		
LED	Black SMD		
Size of Cabinet (W×H×D) (mm)	640 x 360 x 38		
Cabinet Resolution	256 x 144	160 x 90	160 x 90
Weight of Cabinet (kg)	8		
Serviceability	Front		
Contrast Ratio	≥4000:1		
Viewing angle (H/V)	160° / 160°		
Gray Scale (Bits)	12 - 16		
Refresh Rate (Hz)	3840		
Refresh Frame Rate (fps)	50 / 60		
Brightness Level (Manual / Auto / Time) (%)	0 ~ 100		
Color Temperature (Adjustable) (K)	3200 - 9500		
Input Voltage (AC) (V)	90 - 264		
Max. Power Consumption (W/m²)	≤750		
Operating Temperature (°C)	-5 ~ 40		
Storage Temperature (°C)	-10 ~ 50		
Operating Humidity (RH) (%)	30 ~ -85		
Storage Humidity (RH) (%)	30 ~ -85		
Warranty	2 years		

* Parameters above are typical values, which may be adjusted according to actual project requirements.

MODULE VW III



**SIMPLE
INSTALLATION**



**EASY-TO-CONNECT
(PLUG-IN SYSTEM)**



**FRONT
MAINTENANCE**



**SMART
CONNECTION
(CONTROL SYSTEM)**

ASK PHILIPP!

+49 421 83570130
kontakt@pixelbeast.de
www.pixelbeast.de



- 90° installation possible
- Ideal for shop windows and product presentation
- Flexible usage
- High contrast and high clarity



- Wall-mounting or stand-alone-mounting available
- Its the most versatile and the highest-end LED retail Display, applied to multiple high-end brand stores.

- Perfect heat control
- Long lifetime
- Ultra HD visual performance
- Wireless signal transmission between panels: reduce failure rates, fast to install

ASK PHILIPP!
 +49 421 83570130
 kontakt@pixxelbeast.de
 www.pixxelbeast.de



Safety:

- The product is conductive - please keep away from power sources!
- Installation and maintenance may only be carried out by qualified electricians!
- Switch off the display by technical difficulties!
- Don't touch without gloves!



Cleaning:

- Do not clean the display with water
- Do not clean the display directly with a cleaning rag
- Clean dry and carefully